

XR 1000 Spot

Key features:

- Light Source: OSRAM HTI 1000W/PS Lok-it!(5,800K, PGJX36 socket),750 hrs
Or PHILIPS MSR GoldTM 1000 MiniFastFit(6,000K, PGJX36 socket), 900 hrs
- Input Voltages: 200-240V AC, 50/60Hz (optional: 120-240VAC,50/60Hz)
- Power Consumption: 1200W@220V(1266W@120V)
- Strobe: double shutter blades, 0.3-25 F.P.S with macros
- Dimmer: mechanical dimmer 0-100% linearly adjustable dimmer
- Prism: 1x3-facet rotating prism, bi-directional with variable speeds
- Frost: 1 individual frost filter with linear effect
- Iris: 5-100% linearly adjustable iris with Macro
- Focus/ Zoom: motorized linear focus/ zoom
- Light Angle: 9°~60°
- Head Movement: pan 540°, tilt 270° with auto position correction, speed adjustable, with lock mechanism
- Control: DMX512, 3 pins and 5 pins interface
- Channels: short mode 23 channels, standard mode 28 channels and extended mode 35 channels
- Other Functions: DMX512 wireless receiver, DMX512 wireless transmitter(Optional)
- Housing: composite plastic
- IP20
- Net Weight: 31.5kg